



**Crux A1**  
IRD314A







**Crux A2**  
IRD314B

**Crux A1**  
IRD314A

100x100

**Crux A2**  
IRD314B

200x100



**Finish Options**

Trim TW White  
TB Black  
TC Custom

Baffle BW White  
BB Black  
BC Custom

IP Rating 20 IP20  
44 IP44

Unit : MM

**Recessed Adjustable Downlight**

**Illumination Options**



1x10W/2x10W



725lm/1510lm



2700K



15° 24°  
38°



1x10W/2x10W










785lm/1570lm



3000K



15° 24°  
38°



\* All degree & wattage options with photometric data available on request \*  
 \* IP variants & list of accessories for this model available on request \*

**Technical Details**

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	285/534gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

**Accessories**

**Power Options**

- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

- H Honeycomb
- S Softening Lens
- D Diffused Lens
- C Clear Lens
- SNT Snoot

**Other Products in this Series**

**Crux B1**  
IRD314A  
Ø137 - 15W

**Crux B2**  
IRD315B  
L250xW137 - 30W

**Crux C1**  
IRD314A  
Ø175 - 20W

**Crux C2**  
IRD316B  
L325xW175 - 40W

Ordering code : IRDxxxxx(model no)-Tx(trim)-Bx(baffle)xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)-x(filter)  
 Example : {314A/B} {TW} {BW} {20} {2027S} {A} {S}