



360°
Tilt & Rotate

Crux B1
IRD315A



360°
Tilt & Rotate





Crux B2
IRD315B

Crux B1
IRD315A

120x120

Crux B2
IRD315B

230x120



Finish Options

Trim TW White
 TB Black
 TC Custom

Baffle BW White
 BB Black
 BC Custom

IP Rating 20 IP20
 44 IP44

Unit : MM

Recessed Adjustable Downlight

Illumination Options



1x15W/2x15W



1120lm/2295lm



2700K



15° 24°
38°



1x15W/2x15W










1180lm/2355lm



3000K



15° 24°
38°



Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	330/710gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.


Accessories

Power Options

- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

- H Honeycomb
- S Softening Lens
- D Diffused Lens
- C Clear Lens
- SNT Snoot

Other Products in this Series



* All degree & wattage options with photometric data available on request *
* IP variants & list of accessories for this model available on request *

Ordering code : IRDxxxxx(model no)-Tx(trim)-Bx(baffle)xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)-x(filter)
Example : {315A/B} {TW} {BW} {20} {3027S} {A} {S}