





**Crux C1**  
IRD316A



**Crux C2**  
IRD316B



**Crux C1**  
IRD316A

160x160



**Crux C2**  
IRD316B

305x160



**Finish Options**

Trim  TW White  
 TB Black  
 TC Custom

Baffle  BW White  
 BB Black  
 BC Custom

IP Rating  20 IP20  
 44 IP44

Unit : MM

**Recessed Adjustable Downlight**

**Illumination Options**

27W 27S  
27W



1x20W/2x20W



1510lm/3080lm

cct 2700K

2700K



15° 24°  
38°

30W 30S  
30W



1x20W/2x20W










1570lm/3140lm

cct 3000K

3000K



15° 24°  
38°



**Technical Details**

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	380/800gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.


**Accessories**

**Power Options**


- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

- H Honeycomb
- S Softening Lens
- D Diffused Lens
- C Clear Lens
- SNT Snoot


**Other Products in this Series**




Crux A1  
IRD314A  
Ø112 - 10W



Crux A2  
IRD314B  
L210xW112 - 20W



Crux B1  
IRD314A  
Ø137 - 15W



Crux B2  
IRD315B  
L250xW137 - 30W

Ordering code : IRDxxxxx(model no)-Tx(trim)-Bx(baffle)xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-x(filter)  
Example : {316A/B} {TW} {BW} {20} {4027S} {A} {S}

\* All degree & wattage options with photometric data available on request \*  
\* IP variants & list of accessories for this model available on request \*