





**Esquel 1
IRD178**



Tilt & Rotate



Finish Options

Trim TW White
 TB Black
 TC Custom

Baffle BW White
 BB Black
 BC Custom

IP Rating 20 IP20
 44 IP44

Unit : MM

Recessed Adjustable Downlight

Illumination Options

27N	27S
27M	



10W



760lm



2700K



15° 24°
38°

30N	30S
30M	



10W










835lm



3000K



15° 24°
38°



* All degree & wattage options with photometric data available on request *
* IP variants & list of accessories for this model available on request *


Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	270gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

N Non Dimmable
 P Phase Cut Dimming
 A 0-10/ 1-10V Analog
 D DALI Dimming



Other Products in this Series



Ordering code : IRDxxx(model no)-Tx(trim)-Bx(baffle)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-x(filter)
Example : {178} {TW} {BW} {20} {1027S} {A} {S}