





**Esquel 4
IRD181**



Tilt & Rotate



Finish Options

Trim TW White
 TB Black
 TC Custom

Baffle BW White
 BB Black
 BC Custom

IP Rating 20 IP20
 44 IP44

Unit : MM

Recessed Adjustable Downlight

Illumination Options



30W



2280lm



2700K



15° 24°
38°



30W










2505m



3000K



15° 24°
38°



* All degree & wattage options with photometric data available on request *
 * IP variants & list of accessories for this model available on request *

Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	750gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

- H Honeycomb
- S Softening Lens
- D Diffused Lens
- C Clear Lens

Other Products in this Series



Ordering code : IRDxxx(model no)-Tx(trim)-Bx(baffle)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-x(filter)
 Example : {181} {TW} {BW} {20} {3027S} {A} {S}