






**Hypogean R-12**  
ERI608



- Finish FS SS  
FC Custom
- Cable Length C0.5 0.5 Meter  
C1 1 Meter  
CC Custom
- Voltage 24V DC24V  
230V AC230V
- IP Rating 67 IP67











Unit : MM

**Recessed Inground Light**

**Illumination Options**

- |         |              |              |
|---------|--------------|--------------|
| 12W/24W | 840lm/1680lm | 900lm/1800lm |
| 12W/24W | 966lm/1932lm | 480lm/960lm  |

- |       |                        |
|-------|------------------------|
| 2700K | 8° 15° 30° 45° 60° Asy |
| 3000K | 8° 15° 30° 45° 60° Asy |
| 4000K | 8° 15° 30° 45° 60° Asy |
| RGB   | 8° 15° 30° 45° 60° Asy |



\* All degree & wattage options with photometric data available on request \*  
 \* IP variants & list of accessories for this model available on request \*


**Technical Details**

Housing	SS 316 / Aluminum die casting	LOR	~85%
Mounting	Recessed floor mounted	Operating voltage	24V/230V
Light Source	High Power LED	CRI (Ra)	>80
Weight	2350gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~100lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

**Accessories**

- Power Options**
- N Non Dimmable
  - P Phase Cut Dimming
  - A 0-10/ 1-10V Analog
  - D DALI Dimming
- Ingress protection 67 Connectors**
- IC 'I' Connector
  - TC 'T' Connector
  - XC 'X' Connector

**Other Products in this Series**



Remote & Inbuilt Driver Options

Ordering code : ERIxxx(model no)-Fx(finish)-xx(cable length)-xxx(voltage)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-xc(ip connectors)  
 Example : {608} {FS} {C1} {24V} {67} {2427S} {A} {TC}