






Hypogean R-6
ERI606



- Finish FS SS
FC Custom
- Cable Length C0.5 0.5 Meter
C1 1 Meter
CC Custom
- Voltage 24V DC24V
230V AC230V
- IP Rating 67 IP67



Unit : MM

Recessed Inground Light









Illumination Options

- W 6W/12W
W 6W/12W

- lm 423lm/843lm
lm 452lm/903lm
lm 486lm/969lm
lm 243lm/483lm

- CCT 2700K
K 3000K
CCT 4000K
K RGB

- a 8° 15° 30° 45° 60° Asy
a 8° 15° 30° 45° 60° Asy
a 8° 15° 30° 45° 60° Asy
a 8° 15° 30° 45° 60° Asy



* All degree & wattage options with photometric data available on request *
 * IP variants & list of accessories for this model available on request *


Technical Details

Housing	SS 316 / Aluminum die casting	LOR	~85%
Mounting	Recessed floor mounted	Operating voltage	24V/230V
Light Source	High Power LED	CRI (Ra)	>80
Weight	1420gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~100lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

- Power Options**
- N Non Dimmable
 - P Phase Cut Dimming
 - A 0-10/ 1-10V Analog
 - D DALI Dimming
- Ingress protection 67 Connectors**
- IC 'I' Connector
 - TC 'T' Connector
 - XC 'X' Connector

Other Products in this Series



Remote & Inbuilt Driver Options

Ordering code : ERIxxx(model no)-Fx(finish)-xx(cable length)-xxx(voltage)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-xc(ip connectors)
 Example : {606} {FS} {C1} {24V} {67} {1227S} {A} {TC}