







**Hypogean R-9  
 ERI607**



- Finish FS SS  
FC Custom
- Cable Length C0.5 0.5 Meter  
C1 1 Meter  
CC Custom
- Voltage 24V DC24V  
230V AC230V
- IP Rating 67 IP67



Unit : MM









**Recessed Inground Light**

**Illumination Options**

<span style="border: 1px solid black; padding: 2px;">27W</span>	<span style="border: 1px solid black; padding: 2px;">27W</span>	<span style="border: 1px solid black; padding: 2px;">27S</span>	<span style="border: 1px solid black; padding: 2px;">27M</span>	<span style="border: 1px solid black; padding: 2px;">27W</span>	<span style="border: 1px solid black; padding: 2px;">27</span>	<span style="border: 1px solid black; padding: 2px;">Asy</span>		9W/18W
<span style="border: 1px solid black; padding: 2px;">30M</span>	<span style="border: 1px solid black; padding: 2px;">30N</span>	<span style="border: 1px solid black; padding: 2px;">30S</span>	<span style="border: 1px solid black; padding: 2px;">30M</span>	<span style="border: 1px solid black; padding: 2px;">30W</span>	<span style="border: 1px solid black; padding: 2px;">30</span>	<span style="border: 1px solid black; padding: 2px;">Asy</span>		
<span style="border: 1px solid black; padding: 2px;">40M</span>	<span style="border: 1px solid black; padding: 2px;">40N</span>	<span style="border: 1px solid black; padding: 2px;">40S</span>	<span style="border: 1px solid black; padding: 2px;">40M</span>	<span style="border: 1px solid black; padding: 2px;">40W</span>	<span style="border: 1px solid black; padding: 2px;">40</span>	<span style="border: 1px solid black; padding: 2px;">Asy</span>		9W/18W
<span style="border: 1px solid black; padding: 2px;">N</span>	<span style="border: 1px solid black; padding: 2px;">W</span>	<span style="border: 1px solid black; padding: 2px;">S</span>	<span style="border: 1px solid black; padding: 2px;">M</span>	<span style="border: 1px solid black; padding: 2px;">W</span>	<span style="border: 1px solid black; padding: 2px;">Asy</span>			

	636lm/1266lm		8° 15° 30° 45° 60° Asy
	681lm/1356lm		8° 15° 30° 45° 60° Asy
	730lm/1455lm		8° 15° 30° 45° 60° Asy
	366lm/726lm		8° 15° 30° 45° 60° Asy

<span style="border: 1px solid black; padding: 2px;">CCT</span>	2700K		8° 15° 30° 45° 60° Asy
<span style="border: 1px solid black; padding: 2px;">K</span>	3000K		8° 15° 30° 45° 60° Asy
<span style="border: 1px solid black; padding: 2px;">CCT</span>	4000K		8° 15° 30° 45° 60° Asy
<span style="border: 1px solid black; padding: 2px;">K</span>	RGB		8° 15° 30° 45° 60° Asy



\* All degree & wattage options with photometric data available on request \*  
 \* IP variants & list of accessories for this model available on request \*

**Technical Details**


Housing	SS 316 / Aluminum die casting	LOR	~85%
Mounting	Recessed floor mounted	Operating voltage	24V/230V
Light Source	High Power LED	CRI (Ra)	>80
Weight	1405gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~100lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

**Accessories**

- Power Options**
- N Non Dimmable
  - P Phase Cut Dimming
  - A 0-10/ 1-10V Analog
  - D DALI Dimming

- Ingress protection 67 Connectors**
- IC 'I' Connector
  - TC 'T' Connector
  - XC 'X' Connector

**Other Products in this Series**



Remote & Inbuilt Driver Options

Ordering code : ERIxxx(model no)-Fx(finish)-xx(cable length)-xxx(voltage)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-xc(ip connectors)  
 Example : {607} {FS} {C1} {24V} {67} {1827S} {A} {TC}