





**Iota Midi
IRD396**



Finish Options

- Trim TW White
 TB Black
 TC Custom

- Baffle BW White
 BB Black
 BC Custom

- IP Rating 20 IP20

Unit : MM

Recessed Fixed Downlight

Illumination Options



1W/3W



72lm/210lm



2700K



15° 24°
38°



1W/3W










76lm/220lm



3000K



15° 24°
38°



* All degree & wattage options with photometric data available on request *
 * IP variants & list of accessories for this model available on request *

Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	29gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

- N Non Dimmable
 P Phase Cut Dimming
 A 0-10/ 1-10V Analog
 D DALI Dimming

Other Products in this Series



Ordering code : IRDxxx(model no)-Tx(trim)-Bx(baffle)-xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)
 Example : {396} {TW} {BW} {20} {327S} {A}