

**Finish Options**

Trim TW White  
TB Black  
TC Custom

Baffle BW White  
BB Black  
BC Custom

IP Rating 20 IP20

**Iota Mini  
 IRD394**



Unit : MM

**Recessed Fixed Downlight**

**Illumination Options**



1W/3W



76lm/220lm



2700K



15° 24°  
 38°



1W/3W










80lm/240lm



3000K



15° 24°  
 38°



\* All degree & wattage options with photometric data available on request \*  
 \* IP variants & list of accessories for this model available on request \*

**Technical Details**

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	24gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

**Accessories**

**Power Options**

- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

**Other Products in this Series**



Ordering code : IRDxxx(model no)-Tx(trim)-Bx(baffle)-xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)  
 Example : {394} {TW} {BW} {20} {327S} {A}