





**Iota Narrow  
IRD772**



4° Beam



**Finish Options**

Trim  TW White  
 TB Black  
 TC Custom

Baffle  BW White  
 BB Black  
 BC Custom

IP Rating  20 IP20

Unit : MM

**Recessed Fixed Downlight**

**Illumination Options**



4W



475lm



2700K



4°



4W








495lm



3000K



4°



\* All degree & wattage options with photometric data available on request \*  
 \* IP variants & list of accessories for this model available on request \*

**Technical Details**

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	130gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

**Accessories**

**Power Options**

- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

**Other Products in this Series**



Ordering code : IRDxxx(model no)-Tx(trim)-Bx(baffle)-xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)  
 Example : {772} {TW} {BW} {20} {427S} {A}