





Mars Fix Mini
IRD703A



Finish Options



- Trim
- TW White
 - TB Black
 - TC Custom

- Baffle
- BW White
 - BB Black
 - BC Custom

- IP Rating
- 20 IP20
 - 44 IP44

Unit : MM

Mars Fix Max
IRD703B/C



Mars Fix
IRD703

Recessed Fixed Downlight

Illumination Options



7W & 10W/15W



550lm & 780lm/1180lm



2700K



15° 24°
38°



7W & 10W/15W










605lm & 865lm/1295lm



3000K



15° 24°
38°



* All degree & wattage options with photometric data available on request *
 * IP variants & list of accessories for this model available on request *

Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	150/240/280gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.


Accessories

Power Options

- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

- H Honeycomb
- S Softening Lens
- D Diffused Lens
- C Clear Lens

Other Products in this Series



Mars Tilt IRD704 Ø70 - 7W Ø85 - 10W/15W
 Mars Round IRD705 Ø70 - 7W Ø85 - 10W/15W
 Mars Oval IRD706 Ø70 - 7W Ø85 - 10W/15W

Ordering code : IRDxxx(model no)-Tx(trim)-Bx(baffle)-xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)-x(filter)
 Example : {703} {TW} {BW} {20} {727S} {A} {S}