

Finish Options

Trim TW White
 TB Black
 TC Custom

Reflector RS Specular

IP Rating 20 IP20

Opus 1
IRD786



Unit : MM

Recessed Fixed Wallwash Downlight

Illumination Options

27A W 12W

1m 840lm

CCT 2700K






a Asymmetric

30A W 12W

1m 900lm

CCT 3000K

a Asymmetric



* All degree & wattage options with photometric data available on request *
 * IP variants & list of accessories for this model available on request *

Technical Details


Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source COB LED	CRI (Ra)	>80
Weight	220gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

N Non Dimmable
 P Phase Cut Dimming
 A 0-10/ 1-10V Analog
 D DALI Dimming

Other Products in this Series



Ordering code : IRDxxx(model no)-Tx(trim)-Rx(reflector)-xx(IP)-xxxxx(watt+cct+beam angle)-(dimming)
 Example : {786} {TW} {RS} {20} {1227A} {A}