

Finish FS SS

Cable Length C0.5 0.5 Meter
C1 1 Meter
CC Custom

Voltage 24V DC24V

IP Rating 68 IP68

**Shuays R-12
ERU547**











Unit : MM

Recessed Underwater Light

Illumination Options

<table border="1"> <tr><td>30M</td><td>30N</td><td>30S</td><td>30M</td><td>30W</td><td>30</td></tr> <tr><td>40M</td><td>40N</td><td>40S</td><td>40M</td><td>40W</td><td>40</td></tr> <tr><td>60M</td><td>60N</td><td>60S</td><td>60M</td><td>60W</td><td>60</td></tr> </table>	30M	30N	30S	30M	30W	30	40M	40N	40S	40M	40W	40	60M	60N	60S	60M	60W	60	12W/24W/36W	1260lm/2520lm/3780lm 1320lm/2640lm/3960lm	<table border="1"> <tr><td>3000K</td></tr> <tr><td>4000K</td></tr> </table>	3000K	4000K	8° 15° 30° 45° 60° Asy 8° 15° 30° 45° 60° Asy
30M	30N	30S	30M	30W	30																			
40M	40N	40S	40M	40W	40																			
60M	60N	60S	60M	60W	60																			
3000K																								
4000K																								
<table border="1"> <tr><td>65N</td><td>65M</td><td>65S</td><td>65M</td><td>65W</td><td>65</td></tr> <tr><td>RGB</td><td>RGB</td><td>RGB</td><td>RGB</td><td>RGB</td><td>Asy</td></tr> <tr><td>N</td><td>N</td><td>S</td><td>M</td><td>W</td><td>Asy</td></tr> </table>	65N	65M	65S	65M	65W	65	RGB	RGB	RGB	RGB	RGB	Asy	N	N	S	M	W	Asy	12W/24W/36W	1500lm/3000lm/4500lm 720lm/1440lm/2160lm	<table border="1"> <tr><td>6500K</td></tr> <tr><td>RGB</td></tr> </table>	6500K	RGB	8° 15° 30° 45° 60° Asy 8° 15° 30° 45° 60° Asy
65N	65M	65S	65M	65W	65																			
RGB	RGB	RGB	RGB	RGB	Asy																			
N	N	S	M	W	Asy																			
6500K																								
RGB																								



* All degree & wattage options with photometric data available on request *
 * IP variants & list of accessories for this model available on request *

Technical Details

Housing	SS 316 (316L available on request)	LOR	~85%
Mounting	Recessed mounted	CRI (Ra)	>80
Light Source	High Power LED	MacAdam Ellipse	<3
Weight	1530gms	Luminous Efficacy	~100lm/W
Junction Temperature	Tj>75°C (To be used only submerged underwater)	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

N	Non Dimmable
P	Phase Cut Dimming
A	0-10/ 1-10V Analog
D	DALI Dimming

Ingress protection 68 Connectors

IC 'I' Connector	TC 'T' Connector	XC 'X' Connector

Other Products in this Series

Shuays Micro ERU542 Ø42 1W-3W	Shuays R-1 ERU543 Ø65 1W-3W	Shuays R-3 ERU544 Ø115 3W-9W	Shuays R-6 ERU545 Ø160 6W-16W	Shuays R-9 ERU546 Ø160 9W-27W	Shuays R-18 ERU548 Ø200 18W-54W	Shuays L-6 ERU554 L328xW63 6W-16W

Ordering code : ERUxxx(model no)-Fx(finish)-xx(cable length)-xxx(voltage)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-xc(ip connectors)
 Example : {547} {FS} {C1} {24V} {68} {3630S} {A} {TC}