

Finish Options

- Trim  TW White  
 TB Black  
 TC Custom

- IP Rating  44 IP44

**Speck Flat**  
IRD400



Unit : MM

Recessed Fixed Downlight

Illumination Options

27N	27S
27M	



4W



295lm



2700K



15° 24°  
38°

30N	30S
30M	



4W










315lm



3000K



15° 24°  
38°



\* All degree & wattage options with photometric data available on request \*  
 \* IP variants & list of accessories for this model available on request \*

Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	Single source LED	CRI (Ra)	>80
Weight	66gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

- N Non Dimmable  
 P Phase Cut Dimming  
 A 0-10/ 1-10V Analog  
 D DALI Dimming

Other Products in this Series



Ordering code : IRDxxx(model no)-Tx(trim)-xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)  
 Example : {400} {TW} {44} {427S} {A}