





IP65



Finish Options

Housing HG Grey
 HB Black
 HC Custom

IP Rating 65 IP65

Vibrance R1
ESD672A



Ceiling



NA

Unit : MM









Surface Fixed Downlight

Illumination Options

<input type="checkbox"/> 27M 27S		5W	<input type="checkbox"/> 410lm
<input type="checkbox"/> 30M 30S		5W	<input type="checkbox"/> 425lm
<input type="checkbox"/> 30M 30W		5W	<input type="checkbox"/> 460lm

<input type="checkbox"/> CCT 2700K	<input type="checkbox"/> CCT 3000K	<input type="checkbox"/> CCT 4000K
------------------------------------	------------------------------------	------------------------------------

<input type="checkbox"/> 15° 24°	<input type="checkbox"/> 15° 24°	<input type="checkbox"/> 15° 24°
<input type="checkbox"/> 36° 60°	<input type="checkbox"/> 36° 60°	<input type="checkbox"/> 36° 60°




Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Surface - Ceiling / Wall mounted	UGR	<19
Light Source	Single source LED COB	CRI (Ra)	>80
Weight	205gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

<input type="checkbox"/> N	Non Dimmable
<input type="checkbox"/> P	Phase Cut Dimming
<input type="checkbox"/> A	0-10/ 1-10V Analog
<input type="checkbox"/> D	DALI Dimming



Other Products in this Series



* All degree & wattage options with photometric data available on request *
* IP variants & list of accessories for this model available on request *

Ordering code : ESDxxx(model no)-Hx(housing)-xx(IP)-xxx(watt+cct+beam angle)-x(dimming)-x(filter)
Example : {672A} {HG} {65} {527S} {A} {S}