



**Willow Plane
ERW622**




Finish Options

Housing HG Grey
 HB Black
 HC Custom

IP Rating 65 IP65



Wall Recessed



95x50

Unit : MM

Recessed Wall Light

Illumination Options

27
 27




5W



400lm

CCT
 K

2700K



30
 30







5W



425lm

CCT
 K

3000K



* All degree & wattage options with photometric data available on request *
* IP variants & list of accessories for this model available on request *

Technical Details

Housing	Aluminum die casting	LOR	~75%
Mounting	Wall mounted	UGR	<19
Light Source	SMD	CRI (Ra)	>80
Weight	310gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~70lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options

- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

Other Products in this Series



Willow Down ERW696 L171xW106 8W	Willow UP ERW697 L106xW171 8W	Willow Square ERW699 L160xW160 8W	Willow Wall R ESW700 Ø150 - 6W	Willow Wall S ESW701 L150xW150 6W
--	--	--	--------------------------------------	--

Ordering code : ERWxxx(model no)-Hx(housing)-xx(IP)-xxxx(watt+cct+beam angle)-x(dimming)
Example : {622} {HG} {65} {527S} {A}