





**Youvas RA-12**  
ERI611



Finish	<input type="checkbox"/> FS SS
	<input type="checkbox"/> FC Custom
Cable Length	<input type="checkbox"/> C0.5 0.5 Meter
	<input type="checkbox"/> C1 1 Meter
	<input type="checkbox"/> CC Custom
Voltage	<input type="checkbox"/> 24V DC24V
	<input type="checkbox"/> 230V AC230V
IP Rating	<input type="checkbox"/> 67 IP67

External tilting arrangement with Allen key mechanism



Symmetric



Asymmetric



Adjustable



Unit : MM

**Recessed Inground Adjustable Light**

**Illumination Options**

<input type="checkbox"/> 27W	<input type="checkbox"/> 27W	<input type="checkbox"/> 27W	<input type="checkbox"/> 27W
<input type="checkbox"/> 30W	<input type="checkbox"/> 30W	<input type="checkbox"/> 30W	<input type="checkbox"/> 30W



12W/24W



840lm/1680lm  
900lm/1800lm

<input type="checkbox"/> 40W	<input type="checkbox"/> 40W	<input type="checkbox"/> 40W	<input type="checkbox"/> 40W
<input type="checkbox"/> RGB	<input type="checkbox"/> RGB	<input type="checkbox"/> RGB	<input type="checkbox"/> RGB
<input type="checkbox"/> N	<input type="checkbox"/> S	<input type="checkbox"/> M	<input type="checkbox"/> W



12W/24W



990lm/1980lm  
480lm/960lm

CCT 2700K  
 3000K









CCT 4000K  
 RGB



8° 15° 30° 45° 60°  
8° 15° 30° 45° 60°



8° 15° 30° 45° 60°  
8° 15° 30° 45° 60°



\* All degree & wattage options with photometric data available on request \*  
\* IP variants & list of accessories for this model available on request \*

**Technical Details**

Housing	SS 316 / Aluminum die casting
Mounting	Recessed floor mounted
Light Source	High Power LED
Weight	2150gms
Junction Temperature	Tj<75°C
Heat Sink	Al6063

LOR	~85%
Operating voltage	24V/230V
CRI (Ra)	>80
MacAdam Ellipse	<3
Luminous Efficacy	~100lm/W
Life Time	L80-B10 50,000hrs.

**Accessories**

**Power Options**


<input type="checkbox"/> N	Non Dimmable
<input type="checkbox"/> P	Phase Cut Dimming
<input type="checkbox"/> A	0-10/ 1-10V Analog
<input type="checkbox"/> D	DALI Dimming

**Ingress protection 67 Connectors**

<input type="checkbox"/> IC 'I' Connector	<input type="checkbox"/> TC 'T' Connector	<input type="checkbox"/> XC 'X' Connector

**Other Products in this Series**

Youvas RA-3 ERI609 Ø130 - 3W/9W	Youvas RA-9 ERI610 Ø160 - 9W/18W	Youvas RA-24 ERI612 Ø260 - 24W/36W



Remote & Inbuilt Driver Options

Ordering code : ERIxxx(model no)-Fx(finish)-xx(cable length)-xxx(voltage)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-xc(ip connectors)  
Example : {611} {FS} {C1} {24V} {67} {2427S} {A} {TC}