





Youvas RA-24
ERI612



Finish	<input type="checkbox"/> FS SS
	<input type="checkbox"/> FC Custom
Cable Length	<input type="checkbox"/> C0.5 0.5 Meter
	<input type="checkbox"/> C1 1 Meter
	<input type="checkbox"/> CC Custom
Voltage	<input type="checkbox"/> 24V DC24V
	<input type="checkbox"/> 230V AC230V
IP Rating	<input type="checkbox"/> 67 IP67

External tilting arrangement with Allen key mechanism



Symmetric



Asymmetric



Adjustable




Unit : MM


Recessed Inground Adjustable Light

Illumination Options

27W	27W	27W	27W	27W
30M	30N	30S	30M	30W



24W/36W




1680lm/2520lm
1800lm/2700lm


cct	2700K
k	3000K

	8°	15°	30°	45°	60°
	8°	15°	30°	45°	60°

40W	40W	40S	40M	40W
RGB	RGB	RGB	RGB	RGB
N	W	S	M	W











24W/36W



1980lm/2970lm
960lm/1440lm

cct	4000K
k	RGB

	8°	15°	30°	45°	60°
	8°	15°	30°	45°	60°



* All degree & wattage options with photometric data available on request *
* IP variants & list of accessories for this model available on request *

Technical Details

Housing	SS 316 / Aluminum die casting
Mounting	Recessed floor mounted
Light Source	High Power LED
Weight	2450gms
Junction Temperature	Tj<75°C
Heat Sink	AI6063

LOR	~85%
Operating voltage	24V/230V
CRI (Ra)	>80
MacAdam Ellipse	<3
Luminous Efficacy	~100lm/W
Life Time	L80-B10 50,000hrs.

Accessories

Power Options


<input type="checkbox"/> N	Non Dimmable
<input type="checkbox"/> P	Phase Cut Dimming
<input type="checkbox"/> A	0-10/ 1-10V Analog
<input type="checkbox"/> D	DALI Dimming

Ingress protection 67 Connectors

<input type="checkbox"/> IC 'I' Connector	<input type="checkbox"/> TC 'T' Connector	<input type="checkbox"/> XC 'X' Connector

Other Products in this Series

Youvas RA-3 ERI609 Ø130 - 3W/9W	Youvas RA-9 ERI610 Ø160 - 9W/18W	Youvas RA-12 ERI611 Ø210 - 12W/24W



Remote & Inbuilt Driver Options

Ordering code : ERIxxx(model no)-Fx(finish)-xx(cable length)-xxx(voltage)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)-xc(ip connectors)

Example : {612} {FS} {C1} {24V} {67} {3627S} {A} {TC}