





Finish Options

Trim
- TW White
- TB Black
- TC Custom

IP Rating
- 44 IP44

Zenith S2
IRD799

Unit : MM

Recessed Fixed Downlight

Illumination Options

27W	W	15W	lm	900lm	CCT K	2700K	a	100°
30W	W	15W	lm	915lm	CCT K	3000K	a	100°











** All degree & wattage options with photometric data available on request **

** IP variants & list of accessories for this model available on request **

Technical Details

Housing	Aluminum die casting	LOR	~80%
Mounting	Spring - Ceiling mounted	UGR	<19
Light Source	SMD	CRI (Ra)	>80
Weight	285gms	MacAdam Ellipse	<3
Junction Temperature	Tj<75°C	Luminous Efficacy	~75lm/W
Heat Sink	Al6063	Life Time	L80-B10 50,000hrs.

Accessories

Power Options
- N Non Dimmable
- P Phase Cut Dimming
- A 0-10/ 1-10V Analog
- D DALI Dimming

Other Products in this Series

Zenith R1	Zenith R2	Zenith R3	Zenith S1	Zenith S3
IRD795 Ø120 - 9W	IRD796 Ø155 - 15W	IRD797 Ø175 - 20W	IRD798 ☐110 - 9W	IRD800 ☐170 - 20W

Ordering code : IRDxxx(model no)-Tx(trim)-xx(IP)-xxxxx(watt+cct+beam angle)-x(dimming)
Example : {799} {TW} {44} {1527W} {A}